

Hilti TE 76 & TE 76-ATC Combihammer

The complete program that makes a big impact



Technical Data TE 76 & TE 76-ATC

Power input:	1300 W
Voltage:	115 V
Frequency:	50-60 Hz
Hammering speed under load:	Power setting II: 0-2770 blows/min Power setting I: 0-1965 blows/min
Speed loaded:	Power setting II: 0-282/min Power setting I: 0-200/min
Single impact energy:	Power setting II: 6.1 ft-lb Power setting I: 3.1 ft-lb
Tool weight:	TE 76-ATC: 17.4 lb TE 76: 15.4 lb
Dimensions (LxWxH):	TE 76-ATC: 20" x 4.5" x 11.3" TE 76: 19.6" x 4.5" x 10.3"
Drilling range:	1/2" to 6"
Optimum:	7/8" to 1-3/8"
Wood:	Up to 5" hole saw; up to 1-1/4" auger
Steel:	Up to 1/2"
Typical drilling performance in medium-hard concrete:	
3/4" diameter:	Up to 360 mm/min
1" diameter:	Up to 290 mm/min
1-1/4" diameter:	180 mm/min
Typical chiseling performance into medium-hard concrete:	up to 575 cm ³ /min
Minimum distance of hole drilled from wall:	1-1/2"

Advantages

- Active Torque Control for added operator protection (TE)
- Better balance
- Padded rear grip and side handle
- Grippable chuck for bushing applications
- Constant on for chipping applications
- Service indicator light advises user to provide maintenance to reduce down time during critical periods
- Power reduction
- Optimized for operator comfort
- 20% higher performance than its predecessor
- 30% less vibration
- Two year Full Service Tool Support

More benefits to the user

With the TE 76-ATC, Hilti has set new standards in the high-performance combihammer class:

- More protection for the operator
- More versatility for a broader range of applications
- More quality for longer life expectancy
- More comfort to save effort
- More performance for higher work productivity



Wider range of application

- Hammer drilling in concrete, masonry and natural stone from 1/2" to 6" diameter
- Chiselling in concrete, masonry and natural stone
- Setting anchors
- Drilling without hammering using keyed or keyless chucks in wood: 1/2" to 1-1/4" diameter in metal: 1/2" to 3/4" diameter
- Mixing repair mortar using 3" to 6" diameter mixing paddle



Hilti TE 76-ATC Combihammer with slip clutch and ATC

Item No.	Description
00334239	TE 76-ATC Grounded 115 V Equipped with 13 ft supply cord, impact-resistant Hilti case with integrated selector chart, Hilti grease, cleaning cloth, operating instructions

Hilti TE 76 Combihammer with slip clutch

Item No.	Description
00334225	TE 76 Grounded 115 V Equipped with 13 ft supply cord, impact-resistant Hilti case with integrated selector chart, Hilti grease, cleaning cloth, operating instructions

Accessories

Item No.	Description
00334133	Depth gauge For use in setting the desired drilling depth

